

Advanced lubricants for

MERCEDES-BENZ COMMERCIAL VEHICLES

Mercedes-Benz is one of the world's largest truck manufacturers, priding itself on providing operators with the latest, most efficient and reliable vehicles. And as one of the world's top lubricant brands, we are committed to developing the highest quality products that meet and often exceed Mercedes-Benz specifications, providing outstanding performance and protection for your Mercedes-Benz commercial vehicle.

Mercedes-Benz has developed its own specifications (e.g. MB 228.51 for engine oils) and Texaco® products are approved against these key requirements. In addition, our products cover a full range of approvals for other OEMs, meaning that we can meet the demands of a mix of manufacturers as well as your core Mercedes-Benz fleet.



texacodelo.com



Our products suitable for Mercedes-Benz include:

Heavy duty engine oils

Gear oils

Transmission fluids

Total driveline lubricants

Greases

Antifreeze/Coolants

Please see overleaf for a full table of products.

For the latest information on our products,
please refer to the Product Data Sheet (PDS) at:

texacolubricants.com/PDS



FINDING THE RIGHT PRODUCT FOR YOUR MERCEDES-BENZ COMMERCIAL VEHICLE

OEM SPECIFICATIONS RELEVANT PRODUCT(S)		INDUSTRY STANDARDS		PRODUCT ATTRIBUTES	
ENGINE OILS		ACEA*	API*	FUEL ECONOMY	LONG DRAIN
MB 228.61	DELO 400 XSP-FA SAE 5W-30		FA-4; SN	•	•
MB 228.51	DELO 400 RDE SAE 10W-30	E6; E7; E9	CI-4	•	•
	DELO 400 RDS SAE 10W-40	E6; E7; E9	CI-4		•
	DELO 400 SP SAE 5W-30	E6; E7; E9	CI-4	•	
	DELO 400 XLE HD SAE 10W-40	E4; E6; E7; E9	CJ-4		
	DELO 400 XLE HD SAE 5W-30	E4; E6; E7; E9	CJ-4	•	
	DELO 400 XLE SAE 10W-30	E6; E9	CK-4; SN Plus	•	
	DELO 400 XSP-SD SAE 5W-30	E6; E7; E9	CK-4; SN	•	
MB 228.5	DELO GOLD ULTRA S SAE 10W-40	E4; E7	CF		•
	DELO GOLD ULTRA T SAE 10W-40	E4; E7	CI-4		
MB 228.31	DELO 400 LE SYNTHETIC SAE 5W-40*	E7; E9	CJ-4; SM		
	DELO 400 MGX SAE 15W-40	E7; E9	CJ-4; SM		
	DELO 400 XLE HD SAE 10W-40	E4; E6; E7; E9	CJ-4		
	DELO 400 XLE HD SAE 5W-30	E4; E6; E7; E9	CJ-4	•	
	DELO 400 XLE SAE 10W-30	E6; E9	CK-4; SN Plus	•	
MB 228.3	DELO GOLD ULTRA E SAE 10W-40	E7; A3/B4; A3/B3	CI-4		
	DELO GOLD ULTRA E SAE 15W-40	E7; A3/B4; A3/B3	CI-4; SL		
GEAR OILS. TRANSMI	ISSION FLUIDS & TOTAL DRIVELINE LUBRICANTS	ACEA*	API*	FUEL ECONOMY	LONG DRAIN
MB 235.0	DELO GEAR TDL SAE 80W-90^		GL-4; GL-5; MT-1		
	GEARTEX EP-5 SAE 80W-90^		GL-5		
	GEARTEX EP-5 SAE 85W-90*		GL-5		
MB 235.20	DELO GEAR CGA SAE 80W-90		GL-5; MT-1		
MB 235.8	DELO SYN-GEAR HD SAE 75W-90^		GL-5; MT-1		•
	DELO SYN-TDL SAE 75W-90		GL-4; GL-5; MT-1	•	
MB 235.11	DELO SYN-AMT XDT SAE 75W-90		GL-4	_	_
	DELO SYN-AMT XV SAE 75W-80^		GL-4		
MB 235.4/235.41	DELO SYN-AMT XV SAE 75W-80^		GL-4	_	
MB 236.5	ATF HD 389^			_	
MB 236.9	DELO SYN ATF HD				
GREASES					
MB 267.0	DELO GREASE MM EP 2			_	
MB 265.1	DELO STARPLEX EP 2*				
	HYTEX EP 2 LF				
LIEFERVORSCHRIFT DBL 6833.00, BLUE BOOK SPEC 264	MULTIFAK 264 EP 00/000				
WHEEL BEARINGS (SKF)	DELO STARPLEX EP 2^				
	HYTEX EP 2 LF				
ANTIFREEZE/COOLAN		_	_	FUEL ECONOMY	LONG DRAIN
MB 325.3	DELO XLC ANTIFREEZE/COOLANT CONCENTRATE*				

Always refer to the information provided in the operator's manual.

[^] In Chevron's opinion the product is suitable for use in applications where a product of this specification is required.

^{*} Performance – product is either (i) not currently formally approved or certified by the OEM or Industry Standard Organisation; (ii) self-certified; or (iii) was formally approved against an OEM specification which is now obsolete. However, in Chevron's opinion the product is recommended and suitable for use in applications where a product of this specification is required.